

AD-A893 597

NAVAL POSTGRADUATE SCHOOL MONTEREY CA
IMPLEMENTATION OF THE GRAPHICS-ORIENTED INTERACTIVE FINITE ELEM-ETC(U)
SEP 80 J T SHELTON

F/G 9/2

UNCLASSIFIED

NL

1 of 1
ADA
080597

END
DATE
FILMED
2001
DTIC

AD A 093597

LEVEL II

(2)
SC

NAVAL POSTGRADUATE SCHOOL
Monterey, California



DTIC
ELECTE
JAN 09 1981
E

THESIS

IMPLEMENTATION OF THE GRAPHICS-ORIENTED
INTERACTIVE FINITE ELEMENT TIME-SHARING
SYSTEM (GIFTS) ON THE PDP-11.

by

John Trevor Sheldon

September 1980

Thesis Advisor:

Gilles Cantin

Approved for public release; distribution unlimited

DDC FILE COPY

81 1 08 032

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

DD FORM 1473
1 JAN 73
(Page 1)

EDITION OF 1 NOV 68 IS OBSOLETE
S/N 0102-014-6601:

Unclassified
SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE/When Data Entered

20. ABSTRACT (continued)

operating system, are provided. Finally, a systematic approach to building and/or modifying the TITS system in the future is included. The approach taken includes a "File Sorter" program which removes the need for much of the tedious work associated with building the system.

Accession For	
NTIS GRA&I	<input checked="checked" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Avail and/or	
Dist	Special
A	

Approved for public release; distribution unlimited

Implementation of the Graphics-oriented Interactive
Finite Element Time-sharing System (GIFTS) on the PDP-11

by

John Trevor Sheldon
Lieutenant Commander, United States Navy
B. S., United States Naval Academy, 1967
M. S., Naval Postgraduate School, 1972

Submitted in partial fulfillment of the
requirements for the degree of

MASTER OF SCIENCE IN MECHANICAL ENGINEERING

from the

NAVAL POSTGRADUATE SCHOOL
September 1980

Author

John T. Sheldon

Approved by:

Gilles Cantin

Thesis Advisor

Gaust N. Vanderploeghe

Second Reader

J. J. Marto

Chairman, Department of Mechanical Engineering

William M. Tolles

Dean of Science and Engineering

ABSTRACT

The Graphics-oriented, Interactive, Finite Element Time-sharing System (GIFTS), written by Professor A. Kamel and Mr. Michael W. McCabe of the University of Arizona, has been implemented on the PDP-11 at the Naval Postgraduate School. This powerful system of programs was installed in a manner to facilitate its modification in the future. A very brief description of the GIFTS system, including the Unified Data Base, as well as the PDP-11 and RSX-11M operating system, are provided. Finally, a systematic approach to building and/or modifying the GIFTS system in the future is included. The approach taken includes a "File Sorter" program which removes the need for much of the tedious work associated with building the system.

TABLE OF CONTENTS

I.	INTRODUCTION	9
II.	DESCRIPTION OF GIFTS	11
	A. GIFTS DEVELOPERS	12
	B. SYSTEM CAPABILITIES.	12
	1. Pre and Post Processing Capabilities . .	14
	a. Pre Processing	14
	b. Post Processing.	14
	2. Solving Capabilities	15
	C. THE COMPUTER PROGRAM	15
	D. THE UNIFIED DATA BASE.	17
	1. Definition of Terms.	17
	2. Naming Convention.	19
	E. DOCUMENTATION OF GIFTS	20
	1. Reference Manuals.	21
III.	THE PDP-11	23
	A. ORGANIZATION	25
	B. RSK-11M OPERATING SYSTEM	25
	1. LOGON.	24
	2. User Identification Code	24
	3. Peripheral Interchange Program	24
	4. File Transfer Program.	25

5.	FORTRAN Four Plus	25
a.	/CC:20.	25
b.	/CR:NONE.	25
6.	Taskbuilder	25
7.	Librarian Utility Program	26
8.	Text Editor	26
9.	Macro Assembler	26
10.	Execution Command	27
11.	Use of Command Files.	27
IV.	THE BUILDING OF GIFTS ON THE PDP-11	29
A.	SOURCE TAPES	29
B.	SORTING OF SOURCE LISTINGS.	31
1.	Description of FIELTOR	31
C.	TASKBUILDING GIFTS.	34
1.	Non-Overlaid Modules.	34
2.	Overlaid Modules.	37
D.	BUILDING OF LIBRARIES	38
E.	OVERLAY SCHEMES USED.	39
F.	DELETION OF UNNECESSARY FILES	40
G.	REBUILDING GIFTS.	41
V.	PROCEDURE FOR REVISING GIFTS.	42
A.	MAKING MINOR CHANGES.	42
1.	Changing the System Libraries	42
2.	Changing a Module Library	43
B.	MAJOR CHANGES	44
C.	UPDATING OF HELP FILE	45

VI. RECOMMENDATIONS	46
APPENDIX A - DESCRIPTION OF THE GIFTS MODULES.	53
APPENDIX B - LIST OF GIFTS MANUALS	58
APPENDIX C - LISTING OF COMPUTER PROGRAM: FILSOR.	60
APPENDIX D - SAMPLE SESSION WITH FILSOR.	68
APPENDIX E - LISTING OF COMMAND FILE: BUILD.T.CMD.	73
APPENDIX F - LISTING OF GIFTS TAPES (NPS VERSIONS)	82
BIBLIOGRAPHY	85
INITIAL DISTRIBUTION LIST.	86

ACKNOWLEDGEMENT

I would like to take this opportunity to thank Professor Gilles Cantin for his patience and assistance, and Professor Paul Marto who, in Professor Cantin's absence, helped me through a major crisis. Also, there are not words to describe the patience shown by my family through my two tours at the Naval Postgraduate School. They deserve a lot more than merely mentioning their names, but notwithstanding this: Alice, Patricia, John and Peter.

I. INTRODUCTION

The purpose of this thesis is to describe the process whereby the Graphics-oriented Interactive Finite Element Time-sharing System (GIFTS) was implemented at the Naval Postgraduate School.

Anyone who has entered a problem with a large amount of numerical input into a computer knows the fear of making logical or typing errors which will go undetected. The GIFTS system goes a long way in reducing this problem by allowing a user to graphically reproduce the problem he/she has entered into the system. The solved problem can be displayed, as well, in a form which makes the effect of a given loading graphically reproducible at any time in the future.

The first step in building the system was obtaining the latest version (5.02) of the taped program from the Interactive Graphics Engineering Laboratory (IGEL) of the University of Arizona. After an initial attempt at "building" the system on the PDP-11 (using the methods described below) several minor errors were found. These errors were generally in the form of incomplete revisions and were easily correctable with telephone assistance from one of the developers, Mr. Michael W. McCabe, of the University of Arizona.

Since the average mechanical engineering student at the Naval Postgraduate School does not ordinarily spend time being taught on a computer system other than the school's mainframe (currently the IBM 360/67), a great deal of time was required in the preparation for this thesis simply learning the PDP-11/50 and the RSX-11M Operating System. Since it is expected that the GIFTS system will need to be revised in the future, it became obvious that an important objective of this thesis was to develop the means whereby changes to GIFTS could be made as conveniently and "painlessly" as possible without the need for a student or faculty member to become intimately familiar with the PDP-11. It is believed that this objective has been successfully met with the combination of a File Sorter program (FILSOR) and two "command" files. The net impact of these three programs is to allow a most powerful Finite Element Method (FEM) pre and post processor (plus solver) to be completely built on the PDP-11 with two tapes, two commands, and six hours of time.

It is believed that the GIFTS system will, in the future, be an invaluable teaching aid at the Naval Postgraduate School.

II. DESCRIPTION OF GIFTS

GIFTS is a system of programs used in solving Finite Element Problems. This statement does not really do justice to the system for the forte of the system is not in its ability to mathematically solve problems but rather in its ability to reliably and fairly completely define structural problems which are to be solved. It allows a user to:

- 1) Input problem parameters;
- 2) Observe the input both graphically and in tabulated form;
- 3) Update the model; and
- 4) Observe the output

Many problems, due to their sizes, will be outside the range of the "solver" contained in the program. But, due to the highly structured nature of the Unified Data Base (UDB), other systems, more powerful in this area, can access the data, solve the problem, and return the solved problem to GIFTS for display.

The purpose of this section is to give enough of a description of GIFTS and the available documentation to assist a user interested in solving a FEM problem to find out how to get started at the Naval Postgraduate School.

A. GIFTS DEVELOPERS

GIFTS was written by Professor Hussein A. Kamel and Mr. Michael W. McCabe of the University of Arizona. The system is constantly being revised/updated as the need arises. The facility for expansion of the system is built in to it as not all element types have been implemented. As updates are received, they can be implemented by the procedures outlined below in section 7.

B. SYSTEM CAPABILITIES

Much of the information included in this section is already included, in substance, in the "GIFTS Users' Manual." It is the purpose here to synthesize the information from this reference needed to have a general understanding of the system.

A list of the several program modules with descriptions can be found in Appendix A. Each has a purpose in formulating a FEM problem and more than one module is necessary to completely formulate a problem. However, not all program modules are necessary for every formulation.

The general breakdown of the module types/purposes is:

- 1) Model Generation and Editing;
- 2) Load and Boundary Conditions Generation, Display and Editing; and
- 3) General Purpose Computational and Result Display Modules.

In addition, there are modules available (but not yet implemented at the Naval Postgraduate School) to interface the GIFTS system with other Finite Element programs including:

- 1) ANSYS
- 2) SAP4
- 3) NASTRAN

The purpose of these interfaces is to act as "interpreters" of the GIFTS Unified Data Base in order that the generated model may be solved on one of these other systems. The interface program also takes the solutions generated by the other system and formats them back into the UDB for GIFTS in order that they can be displayed.

In the "GIFTS Users' Reference Manual," it is stated: "the generation and display capabilities of GIFTS go beyond its own analysis capabilities." It gives, by example, the fact that the GIFTS system can generate and display higher order elements while not (yet) being able to analyze the results. Though the author is not privy to a timetable, it is expected that the system capabilities will increase and can be added to existing capabilities currently at the Naval Postgraduate School. The methodology for making such revisions is covered below in chapter V.

1. Pre and Post Processing Capabilities

a. Pre Processing

The GIFTS system is capable of being used as a pre-processor for other systems. It accepts commands which allow a user to establish the geometry of a model and to display it at a terminal for verification.

Figure 1 is an example of the program/user interaction which is required to establish the geometry of a plate with a hole in the center.¹ Figure 2 is the resulting plot with elements and points labelled. Should an error be made during the session, a correction can be made before going on.

Also available to the user are a variety of tabulations of input and computed data. These also prove useful in the verification of a model.

b. Post Processing

Figure 3 depicts the results of the solved FEM problem which was entered as in section 1.a. above. It depicts the stress contours as computed by (in this case) the GIFTS system for a given loading. If a different solver (e.g. SAP4) were to be used, the interface program would "translate" the output from the solver into the

¹This problem is one that was included in the "GIFTS Primer" which was written at IGEL, University of Arizona. See Appendix D.

GIFTS UDB format before using the GIFTS modules for displaying the results.

The system can also display deflection plots due to a given loading as well as computing and displaying time domain problems.

2. Solving Capabilities

The system, as presently configured, is capable of solving a wide class of structural, finite element method problems. However, there are some limitations. Page III-1 of the GIFTS User's Manual lists those elements which enjoy "Full Support" and, also, those within the categories: "Generation and Display Only" and "Storage Only." A user should be aware of these distinctions before deciding to solve a problem completely by GIFTS or by GIFTS in conjunction with another system.

3. THE COMPUTER PROGRAM

If loaded all at once, with no overlaying, the entire set of program/modules would take up to perhaps two mega bytes of memory. Since it is not desirable (or usually possible) to have this much space available to a user, the program has been divided into several, separately executable modules having as their common denominator the Unified Data Base.

Each program is called up (executed) by a "RUN" command. At the end of the session with an interactive module, a

"QUIT" (or similar) command is given which causes the module to update the data base, close files and leave the module. To enter the next module another "QUIT" command is given and so forth.

The interactive modules accept a large number of well-defined commands. Some of the modules have similar and even duplicative sub-objectives and therefore contain many of the same commands. Each program, however, has its own communications subroutine which will accept commands only valid in the particular module. Several different type prompt symbols are used (>, *, ?, blank) which make the nature of the input (i.e. alphanumeric, integer or floating point) less ambiguous.

As it was earlier stated, overlaying is required for most modules when installed on the PDP-11. This is due to a 64K byte limitation for any program segment. The overlaying schemes used for the several modules were included on the tapes received from the IGDL, University of Arizona, and are duplicated on the tapes discussed below in section IV.C.

One of the capabilities available to the user in many modules is that of plotting the model at a terminal. This feature obviously requires that a terminal with a graphics capability be used. The terminal for which the GIFTS System at the Naval Postgraduate School (NPS) is presently

geared is the Tektronix 4000 Series. To change to another type of terminal would require modifications to several of the GIFTS library subroutines.²

D. THE UNIFIED DATA BASE

During the course of model definition, the GIFTS system opens, performs input/output (I/O), and closes files on disc. At the end of a session one will find on his/her disc space several files having the jobname (specified by the user) as their filenames but each having a different "extension." These files represent the Unified Data Base (UDB).

The UDB files created by GIFTS are primarily random access, unformatted disc files. The fact they are unformatted makes storage of numerical data more efficient and the random access feature allows for easier identification of a particular record to be read or written.

1. Definition of Terms

The individual files are described in the "GIFTS Systems Manual" but a general description of the methodology of the programmers and the terminology used in the manual is warranted.

A "physical record," in context with the terminology used in the Systems Manual is the "collection of data" found

²Specifically those in the file: GIFTS.PDP

in one record. When submitting a program written on punched cards, the input record length is limited to 80 - the number of characters allowed on the card. A disc, of course, does not have this limitation and the record size can be extremely large. (In the GIFTS system, the record size is automatically defined within the program and can be as large as 1634 bytes.) The program uses equivalent size buffers to accomodate the I/O record sizes and also allows for variable sizing of buffers/record size should the programs be run on a large machine. This fact is academic though since the current installation at the Naval Postgraduate School is on the PDP-11.

A "logical record" is a term used for the grouping together of data which are related insofar as the programmer says they are. Better put: "the smallest collection of data into which the data contained in a file may be divided." For example, a physical record of 200 bytes could be divided into ten logical records of 20 bytes each. In this case, the number "10" is the "blocking factor."

Data in GIFTS are generally buffered in named COMMON. A buffer typically consists of a physical record plus some "bookkeeping" data. For example, a physical record in the "points" (PTS) file contains data on ten points. If the point being worked on by GIFTS is not in the record currently in the buffer, the current buffer is

stored in the PTS file and the correct record is read in. The "logical record" needed by GIFTS (i.e. the point being worked on) is now available.

2. Naming Convention

The UDB consists of, typically, ten or so files (the exact number depending on the problem being modeled). Certain administrative files are kept open throughout the life of a problem - that is, until deleted by the user. These files do not contain data which are used directly in solving or displaying a specific model. Other files are temporary or "scratch" files and are deleted prior to leaving the module which opened them. Then there are the files containing the data unique to a model which are "passed on" from module to module until the model/solution is completed. All of these files are the Unified Data Base - the focal point of the GIFTS system.

At the beginning of each module, the user is queried concerning the name of the model. The first time that this name is used (usually in the modules BUILD or EDIT), the name becomes unique until the problem is deleted from the disc.³

Figure 4 is a sample listing of the files built by GIFTS for the job "PLATE" which was shown in previous

³This cannot be done by GIFTS but must be done with the file handler - see section III.C.3.

section. As the problem progresses, the number of files could increase and eventually take up a great deal of disc space (users should keep this in mind when creating a problem when disc space is at a premium).

Two other files exist which do not follow the naming convention which was outlined above. These are: `GIFTS5.INF` and `GIFTS5.EST`. The former is a sequential, formatted file listing all the "HELP" command answers that are available. It requires updating as changes are made to the system and is not tied to any particular problem. The latter file is used by OPTIM (i.e. optimization program) and is strictly for time estimates for the problem being completed. The user normally need not be concerned with this file, as it should already exist. If it doesn't, this will cause minor problems and could be easily rebuilt by running the module `EST.TSK` which is included on the magnetic tapes discussed below in section IV.3.

Each of the files is described in the GIFTS System Manual beginning on page SM II-2. For those interested in modifying the GIFTS system or writing an interface program, further explanation of the UDF is given below in section IV.

E. DOCUMENTATION OF GIFTS

The source listing as provided by the IGEL, University of Arizona, is liberally filled with comment statements. However, the interaction of the approximately 300 library

subroutines with the program and subroutines within the modules is so complex that trying to understand exactly what a program is doing at a particular time is virtually impossible without an excessive expenditure of time.

The user normally will not be interested in the source listing but rather in how to RUN the system. The remainder of this section is devoted to the documentation provided by the developers on how to use the system to solve a problem.

1. Reference Manuals

There are several manuals which are of interest to both the GIFTS user and the systems analyst responsible for building or maintaining GIFTS (see Appendix E). The manuals are provided with the GIFTS system by the University of Arizona and are kept at the Naval Postgraduate School in the Mechanical Engineering Department Computer Laboratory, Room 201D, Halligan Hall.⁴

Two of these manuals have already been mentioned above: "The GIFTS Systems Manual"; and the "GIFTS User's Reference Manual." The former was used extensively in attempting to understand how the computer program worked and to understand the UDB. The latter was used in conjunction

⁴Not all the manuals have been provided by IGEL, University of Arizona, as they are yet to be written. For example, the "GIFTS System Installation Manual," which would have been useful here, has not yet been completed.

with the "GIFTS Primer" to obtain an understanding of how the system operated from the user's viewpoint.

The "Primer" serves as an excellent aid for the cautious, first-time user to get some hands-on experience with the system and to see what the system can actually do. It also explains, in detail, the purpose of several of the commands. The included examples, besides being educational for the first-time user, are very useful in checking the installation for accuracy.

III. THE PDP-11

The GIFTS system has been installed on the PDP-11/50, located in Room 500, Spanagel Hall, at the Naval Postgraduate School. The choice to install the system on this particular computer was based on its availability; the fact that GIFTS had already been brought up on the PDP-11 elsewhere; and, that the main computer system at NPS, the IBM 360, was being replaced in the near future.

There are actually two PDP-11s available in the Computer Lab: one with the UNIX operating system, and the other with RSX-11M. GIFTS was installed in the latter as it is limited to 32K work (64K byte) segments whereas UNIX allows only a 16K work (32K byte) segment size.

A. ORGANIZATION

The Computer Laboratory at the Naval Postgraduate School falls under the administrative control of the Director, Computer Laboratories. Under his/her control are several analysts/mathematicians familiar with the RSX-11M operating system.

B. RSX-11M OPERATING SYSTEM

The following are descriptions of utilities available under RSX-11M and which are used in the building and running

of GIFTS. The descriptions are provided here primarily as background information for section IV. The details of the following utilities may be found in the appropriate PDP-11 manuals.

1. LOGON (HEL)

"HEL" is the logon keyword. For the Mechanical Engineering Department, the logon is "HEL MEDEPT" whereupon the computer queries the user for an appropriate password. The logoff "keyword" is simply "BYE."

2. User Identification Code (UIC)

The UIC is assigned by the Director, Computer Laboratories, and serves two primary purposes in the RSK-11E operating system:

- a. Identification of a particular user for security and accounting purposes; and
- b. Identification of the user's directory on disc.

3. Peripheral Interchange Program (PIP)

PIP is the very versatile system of file handlers which is used to: move, delete, copy, rename, etc., files created on disc.

Some knowledge of PIP is essential to any prospective user of the GIFTS modules on the PDP-11. It allows for deleting and transferring files - which are useful "house-keeping" functions to know.

4. File Transfer Program (FLX)

FLX is the PDP-11 utility for handling files between disc and magnetic tapes.

5. FORTRAN Four Plus (F4P)

The FORTRAN compiler used to build the GIFTS system. The syntax for this system allows for the use of many "switches." In the building of GIFTS on the PDP-11 it was only necessary to use two switches:

a. /CO:20 - This switch was necessary on several of the subroutines to increase the number of allowed continuation cards from the default (i.e. 5).

b. /TR:NONE - This switch was used to build a separate system library which did not include the code necessary for tracing in the event of an object time error. This omission is necessary to allow the two largest modules to fit into the 32K word allowable segment on the PDP-11. (This will be further explained in section IV below.)

6. Taskbuilder (TKB)

TKB is the "linker" used under RSX-11M. In conjunction with command files, it builds executable modules complete with overlays. A description of the command files used for building GIFTS is given in section IV. Further knowledge of the TKB utility would only be necessary if one were to rebuild or modify the GIFTS system without the help of the techniques which will be demonstrated in section V.

7. Librarian Utility Program (LBR)

This utility is used to create and modify libraries of files. In the case of the building of the GIFTS system, it is used to create "system" and "module" libraries. In modifying the GIFTS system one would only need to become familiar with the syntax of two "switches": /IN = (that is, "insert"); and /DE: ("delete").⁵ Examples are shown in section V.

8. Text Editor (EDT)

The RSX-11M system at the Naval Postgraduate School offers two text editors. "EDT" was selected because of its power. With a little imagination, a great deal of time can be saved in making major and/or repetitive changes to a file with EDT. To make future revisions to GIFTS, it is quite obvious that a knowledge of an editor would be necessary.

9. Macro Assembler (MAC)

This is the keyword for assembling macro programs. For example, to assemble a program called TEST.MAC, one could enter:

```
MAC TEST = TEST
```

This would produce an object module called TEST. It is also possible to get a listing of the program with all external

⁵Note the syntax difference in the use of "=" for /IN and ":" for /DE.

references, etc. For details concerning this and other features, a user should refer to the appropriate PDP-11M manual.

10. Execution Order (RUN)

RUN is the command under RSK-11M which causes an executable module to be loaded and executed. For example: RUN BULKM. For files that are overlaid, the executable module (with a default file extension of TSK) will need an additional file with the extension "STB." This is the "symbol table file" which is also built at the time of taskbuilding.

11. Use of Command Files

"Command" files are ASCII formatted files having an extension of ".CMD." A Command file is executed by simply inserting the character "@" before the filename. For example, to run a command file called GIFTS5.CMD, one would type in:

@GIFTS5

The contents of the file would be executed line by line.

Another way in which command files can be used is in conjunction with a utility or the FORTRAN compiler, F4P. For example, if there are two separate FORTRAN programs to

be compiled, TEST1.FTN and TEST2.FTN, one could edit a command file called TEST1.CMD as follows:

```
>EDT TEST1.CMD
*I
TEST 1 = TEST 1
TEST 2 = TEST 2
{ctrl}Z          6
*exit
To execute this command file, one types:
```

F4P QTEST1

This method can also be used for: PIP, TKB and LBR.

⁶CTRL Z is the combination of characters which allows the user to leave the "input mode" in EDT.

IV. THE BUILDING OF GIFTS ON THE PDP-11

The process of building GIFTS can be broken down into a few logical steps:

- 1) Sorting
- 2) Compiling
- 3) Library Building
- 4) System Building
- 5) Cleanup

To simplify some of these time consuming processes which must be completed, the author has written a "File Sorter" program (FILSOR) which effectively reduces the "slave labor" time and improves, it is believed, the accuracy of this process.

A. SOURCE TAPE

The PDP-11 version of the GIFTS system arrived on an unlabelled, ASCII-formatted, nine-track tape. Along with the tape was a listing of the names of the files and the sizes thereof. The files can be broken down by type as follows:

Concatenated FORTRAN programs/subroutines:	29
Overlay Description Files:	15
Macro Programs	2
GIFTS Information File	1
Test Programs (FORTRAN)	3

The listings of FORTRAN programs/subroutines are unusable in the form they are received and must be separated, compiled, and the object code placed in libraries before the taskbuilding (linking) process can even begin. The steps that would be involved if this separation process were to be done manually with the Text Editor (EDT) are:

1. Find the first line of the program, subroutine or function; then
2. Find the last line of the program, subroutine or function (i.e. "END"); then
3. Write the inclusive lines between the first and last lines out to a new file; then
4. Go back to 1. until an EDF is reached.

The finding of the first and last lines using EDT is not difficult (except in each case, one must look for either a subroutine or a function since both occur). Writing to a new file is not particularly difficult but requires a rather lengthy line of commands. For example, to write lines 10130 through 13450, inclusive to a new file named FILEMAN.FIN, requires:

```
WR10130:13450/PI:FILEMAN.FIN/IN
```

It can be imagined how long it would take to do this hundreds of times (about six hundred for GITS) without an error! For the reason that this task is so tedious and fraught with peril, the author wrote FILESOR.

B. SORTING OF SOURCE LISTING

1. Description of FILSOR

The basic FILSOR program accepts as input, the name of a source listing file⁷ containing at least two subroutines or one main program plus one or more subroutines (or functions). The following restrictions or guidelines concerning the use of FILSOR exist:

- a. There are no "Block Data" subroutines within the source listing to be sorted;
- b. If a listing contains a main program (vice a subroutine or a function), it must appear first in the file;
- c. In all cases, the sorted program, subroutines and functions will have to be compiled;
- d. In some cases, entire systems of sorted subroutines will have to be compiled with the "/TR:NONE" switch in use;
- e. In all cases, the sorted and compiled subroutines will have to be stored in a library called, arbitrarily, I1.OIP;
- f. Comment cards preceding the first executable statement are discarded from the first output program;

⁷The current version of the GIFTS source listings are on a magnetic tape in a format useable under the FIM utility of the RSX-11M operating system (see above, section III.C.4). To obtain a listing of a particular magtape file, it would be necessary to load the file onto disc using FIM and then printing it using PIP.

- g. The input listing is unaffected by FILSOR;
- h. The "END" statement images must begin in column seven (otherwise the program will fail to recognize it as being the last statement in the program).

All the FORTRAN source listings included with GIFTS conform to the above restrictions.⁸

The main output from FILSOR is, of course, the separated FORTRAN files. The files are named according to the subroutine/function name or, in the case of a main program, the name of the input file. For example, assume a file named EXAMPL.EXT contains: a main program and three subroutines (subroutines TEXT1, TEXT2 and Function TEXT3). The results of running EXAMPL.EXT through FILSOR would be to create four new files called:

```
EXAMPL.FTN  
TEXT1.FTN  
TEXT2.FTN  
TEXT3.FTN
```

The original file EXAMPL.EXT, containing the concatenated FORTRAN files, still exists and is unchanged by running FILSOR.

⁸It should be emphasized that in the first program or subroutine in the file, blank or comment cards preceding the first executable statement will be "lost." Similarly, blank or comment cards between "END" and the next subroutine or function within the listing will be lost. Both these statements apply only to the sorted routines - not the original listing.

FILSOR also builds two additional files while sorting the input file. Since it will eventually be necessary to compile all the subroutines, a file called LIB.CMD (a command file) is built which allows for the compilation of all program/subroutines sorted by FILSOR. As stated in section III.B.5, two possible combinations of "switches" occurred in the building of GIFTS: one with the "/TR:NONE" switch, and one without. The "/CO:20" switch was used regardless. FILSOR queries the user in order to determine whether he/she wants to include the trace capability or not.

The other file built by FILSOR is called "STUFF.CMD." This file, in conjunction with the IER utility, will store the object modules compiled with LIB.CMD into an object library called L1.OLE. After the "STUFF" process, the library L1.OLE can be renamed using PIP to avoid confusion with future FILSOR operations.

Appendix C is a complete listing of FILSOR. An example session is included in Appendix D.

A more complicated version of FILSOR which allows a user to setup an input file with a list of several input files to be sorted is also included on magnetic tape.⁹

⁹This version is called FILSA2 and requires an additional program, STUFFE, to build the input file. Both of these modules are included on tape and are executed as a part of the automatic "BUILDIT" command file discussed below in section V and listed in Appendix E.

1. BUILDING GIFTS

Most GIFTS modules must be overlaid on the PDP-11 in order that they can fit into memory. The syntax involved with the taskbuilder is quite extensively described in the PDP-11 manuals and will not be duplicated here. Several examples of the syntax will be shown and by these means the reader will be able to appreciate the methodology used on the PDP-11.

1. Non-Overlaid Modules

At present, there are seven modules which are not overlaid and, therefore, are the simplest to "build." It is only necessary to compile these modules and taskbuild (building an executable module and "linking" with external references). To simplify the process even more, command files are normally used for the process and were used for building GIFTS.

For example, the module PRINT is built using the following Command file:

```
PRINT/ P/CP=PRINT,HIWID/11  
/  
ACCTIV=15  
PAGEU =900  
UNITS=15  
ASQ="I:6  
ASB=SY:7:8:9:10:11:12:13  
ASB=SY:14:15  
//
```

The switches used in the main line of the Command file are necessary and more or less "boiler plate" switches. They

are explained in detail in the PDP-11 manuals. The expression "GIFTHIB/ 0" in the file indicates to the taskbuilder that besides the PDP-11 system library, (on the PDP-11, this is SYSLIB.OLB and need not be referred to in the Command File as it is automatically called by TMB), a library called GIFT IB.OLB is called in order to resolve any external references. GIFTIB.OLB is actually made up of the compiled object modules from the following seven MITS tape files:

```

MIB11.OLB
MIB12.OLB
MIB13.OLB
MIB14.OLB
MIB15.OLB
MIB16.OLB
MIB17.OLB
MIB18.OLB

```

The other lines in the command file for MITS do warrant some explanation as they are controlled by the MITS system size and parameters within the program. It is quite possible that the parameters in the existing command files could change in the future as the MITS system is updated/modifed.

The term "MAXBUF" designates the size of the I/O buffer. The recordsize for several of the MITS files is quite large (up to 1634 bytes) but since not all files are called by every modules, MAXBUF will vary between modules. The size of MAXBUF for a particular module can be computed by referring to the table on page M-11.2 of the MITS Systems manual.

"UNITS" defines the maximum number of the logical units whereas "ACTFIL" assigns the number of active files which can be concurrently open. The latter is variable between modules and is quite important since the ACTFIL parameter causes allocation of memory at the time of task-building. As many of the modules are quite tightly "packed" into the 32K word allowable memory segment, the extra bytes available by adjusting this parameter become very important.

"ASG" fulfills the taskbuilder requirement that each logical unit have assigned to it a physical unit. Thus, in the PRINT command file, logical unit six is assigned (ASG) to the terminal (TI:) and all TT's between seven and 15, inclusively, are assigned arbitrarily to the "system" disc (SY:).

Without the command file, each of the steps would have to be individually typed in. Since a command file was built in this case, it is merely necessary to type:

```
tkb print
```

It is worth noting here that if several modules are to be built, the command files may be imbedded in another command file. For example, take the command file GROUP.COM which is made up of:

```
tkb print
tkb savek
tkb residu
```

This file can be executed by typing: group.

2. Overlaid Modules

The majority of the GIFTS modules are overlaid. Some of the overlay schemes are fairly complicated and are difficult, due to the taskbuilder syntax, to enter at a terminal. Therefore, as with the non-overlaid modules, command files are used. However, now "indirect" or "Overlay Description" files using "Overlay Description Language" (ODL) are also used. (These files are commonly referred to as "ODL files.")

The ODL file is built with the text editor for each module and describes the overlay scheme for the module. The file is then referred to by the TMS command file. For example, the following is the command file used to build the module BULK in GIFTS. Notice on the right hand side of the equal sign is the expression: BULK/MP. The /MP switch indicates to TMS that there exists a file on disc called "BULK.ODL" which describes the overlay scheme for the module (Figure 5). Note that no object modules are referred to directly in this command file:

```
BULK /MP/OP,,BULK=BULK/MP
LDEFIL=13
LXPR=900
LHIC=15
LH=TI:6
LH=SH:7:8:9
LH=SH:10:11:12:13:14:15
//
```

The first line in the ODL file indicates the overlay scheme in symbolic terms (i.e., A, B, C, etc.). The other lines

indicate the choice of object modules for the "Aoot" and the various overlays. There are syntax and command rules which obviously must be followed in building an ODI file. Such information is found in: "RSX-11M Task Builder Reference Manual." It is not the purpose here to elaborate on this syntax.

The Command and ODI files for building GIFTS exist for all overlaid modules and are on magnetic tape for the eventuality that the system will need to be rebuilt. These files are the core of the work necessary for building GIFTS. Anyone interested in vastly revising GIFTS would need to know the existing structure of GIFTS and then attempt to reconstruct the effect of the revisions on the size of modules. As stated above, some of the modules are very tightly packed, some taking up to greater than 99 percent of the available 32K words.

2. BUILDING OF LIBRARIES

There are two basic types of libraries built from the GIFTS files. The first type includes the two separate system libraries. The reason for having a second "system" library is that two GIFTS modules, BULKLIB and RESULT, simply cannot fit into 32K words as normally built. Thus, a second nearly duplicate library is built using the "/TA:NON" switch when compiling. The effect of this switch is to reduce the size of the object module by about ten percent.

The absence of the "trace" capability means that should an error occur during program run time, the system will not inform the user in which object module the error occurred. Again, this "problem" occurs only in FULLER and RESULT.

The other type of library is called a "module" library. That is, for every executable module where overlaying is being used, a library of the object modules derived from the individual program listing (vice the GIFTS system library listings) is built. This approach allows the analyst to "keep track" of which object modules are needed for each overlaid module. Thus, this is a matter of convenience.

In Figure 5 are examples of how the two library types are used. Note that in every case where the switch "/LB" is seen, the preceding filename is the name of an object library. Where the switch "/LB" is used alone, as in:

IPFULLER/LB, the meaning is that a check through the library GIMFWID.OLB will be made to resolve references. Where a colon is attached (i.e. "/LB:"), the FULLER system will expect to find one or more specifically named object modules which are to be designated as being part of a particular segment.

E. OVERLAY SCHEMES USED

The magnetic tape received from INMIL, University of Arizona, included the overlay schemes used at the Naval

Postgraduate School for the building of GIFTS. The schemes are actually in ODL file form. Changes to the overlay scheme(s) would be completed by making revisions to the respective ODL file and then rebuilding the respective module(s).

Installing the GIFTS system on another computer system could necessitate a revision to the schemes but the ODL files are a good point for departure.

F. DELETION OF UNNECESSARY FILES

Along the path of building GIFTS, one accumulates several files that are extraneous to the actual running of the GIFTS system. If file deletions are not completed, an accumulation of about 16,000 blocks of intelligence on disc (about twenty percent of the maximum capacity of the CDC 9762 disc drive) would be taken up by GIFTS. Since the executable module files accumulate to only about 4000 blocks, file deletions (using PIP) should be completed.

The method for doing this on the PDP-11 can be found in the appropriate PDP-11 Manual. Generally, it takes the form:

PIP Filename.Extension;Version/DE

"Wild cards" are permitted for filenames, extensions and version names/numbers. The version number (or wildcard) must be included.

G. REBUILDING GIFTS

A.. files necessary to rebuild GIFTS exist on two magnetic tapes. A listing of the contents of the respective tapes are included as Appendix F. To rebuild GIFTS, it is merely necessary to load the tapes and type the following two commands:

```
FLX /RS=MT1:[*,*] BUILD.CMD/EO  
BUILD
```

The resulting process takes approximately six hours to complete. A listing of BUILD.CMD is included as Appendix F.

V. PROCEDURE FOR REVISING GIFTS

A. MAKING MINOR CHANGES

It should be remembered that each module is listed separately. In addition, there are five files of subroutine listings plus two assembly language files which are included as part of the GIFTS system libraries (two). It should be quite obvious that if a revision to a single module listing is necessary then only that module will need to be rebuilt.

On the other hand, if one library subroutine is changed it would be wise to rebuild the entire system (unless the modules containing the revised subroutine can be isolated).

1. Changing the System Library

The following steps should be completed in revising the system libraries:

- a. Edit (EDT) the listing (either LIBR1.NEW, LIBR2.NEW, LIBR3.NEW, LIBR4.NEW or LIBR5.PDP);
- b. Extract the subroutine(s) which have been revised (in order that the entire library need not be rebuilt);
- c. Compile the subroutine twice-once with the /CO:20 switch alone and again with the /TR:NONE switch;

d. Insert the object modules into the two libraries - GIFTLIB and GLIB2 by using the LER utility;

e. Rebuild the GIFTS system.

The last step is not quite as difficult as it seems since the command and ODL files are already built for this purpose. The entire rebuilding process can be done by a series of TKB "@" statements. Such a command file, called GIFTS5.CMD, is shown in Figure 6 and is included on the tapes mentioned in section IV.G. By merely typing @GIFTS5, the entire GIFTS system will be built in approximately one hour. The file depends, of course, on the existence of the command files, ODL files, GIFTS system libraries, and the respective module libraries to execute. A listing of the files needed to execute GIFTS5.CMD are shown in Figure 7.

2. Changing a Module Library

If only a single module listing is revised, then it should not be necessary to build the entire GIFTS system. In other words, the use of BUILD.CMD is unnecessary here. Instead, it would only be necessary to execute the steps which are demonstrated in Appendix D. The OPTIM module is used by way of example in Appendix D, but any overlaid module would be "rebuilt" in the same manner.

For non-overlaid modules, it is necessary only to compile¹⁰ and taskbuild using the provided command files.

E. MAJOR CHANGES

If a substantial number of changes to the GIFTS system were to be made, it may be necessary to rebuild the entire set of executable modules. Assuming that the command files are not to be revised,¹¹ the following steps would be followed:

1. Revise the respective listing(s) using the Text Editor (EDT);
2. Revise the two tapes using FLX;
3. Execute @BUILD.T.

It should be obvious that if the two existing tapes are to be modified that a new set of tapes will need to be built. The FLX utility is the handler for this process. It should be noted that the present command file, BUILD.T, is based on the existence of two separate tapes with the contents being as listed in Appendix F. In this appendix,

¹⁰It should be remembered that the default extension for a FORTRAN file on the PDP-11 is ".F". The FORTRAN listings provided by IGEL had the extension ".NEW." Therefore, when compiling these programs using the F4P compiler, use syntax as follows (for the file called REDCS.NEW):
F4P REDCS=REDCS.NEW.

¹¹If new subroutine(s) were added to an individual module, then the respective "ODE File" would also need to be revised. It is also possible that changes to existing subroutines could make the individual module greater than 32K with existing overlay schemes. Then, a revised scheme may be necessary and the ODE file would have to be revised.

it should also be noted that the VIC for the tape file is:
[20,1]. This VIC is presumed when BUILD7 is executed.

C. UPDATING OF HELP FILE

There exists a file called GIFTS5.INF which contains the information or data used by the "HELP" command from the various GIFTS modules. It will be necessary to use an editor to change this file. Revisions would be needed to this file only if updates were received from the University of Arizona.

VI. RECOMMENDATIONS

Several possibilities exist at the Naval Postgraduate School for the enhancement of the GIFTS system. A TEKTRONIX 4081 computer is already present within the Mechanical Engineering Department and could be used as an intelligent terminal. That is, it would be possible to operate with some of the GIFTS modules on a host computer such as the PDP-11 with the smaller modules being used independently on the 4081.

Of course, when the new mainframe replaces the currently used IBM 360/67 in FY 1981, a worthwhile project would be to install GIFTS on it.

In addition, it is recommended that the interface program for the SAP4 system, which is currently available at NPS, be obtained from IGEL, University of Arizona, in order that the SAP4 and GIFTS can be "tied together."


```

* CARC
> C12
? 1,6,2,7
>
* COMPLINE
> L35
? L34,L45
>
* GETY
> QM4
? 1,1
* GRID4
> QUARTER
? C12,L23,L35,L15
>
* KN
* LNAM
* CNAM
* PLOT

```

```

BULKM VER. 5.02
TYPE JOB NAME
PLATE
JOB PLATE BEING CREATED
* MSTEEL
> 1
>
* ETH,1
> 1
? 0.1
>
* KPOINT
> 1
? 2,,
> 2
? ,2,
> 3
? ,6,
> 4
? 6,6,
> 5
? 6,,
> 6
? 1,414,1,414,
>
* SLINE
> L23
? 2,3,5
> L15
? 1,5,5
> L34
? 3,4,4
> L45
? 5,4,4
>
*

```

Figure 1 - Program Interaction for PLATE




Figure 2 - GIFTS Presentation of PLATE Input




Figure 3 - CITS Presentation of Stress Contours JOB PLATE

>PIP PLATE */LI

DIRECTORY DP3 [20.1]
23-AUG-80 13.17

PLATE FIL.1	1	23-AUG-80	12	07
PLATE MAT.1	1	23-AUG-80	12	07
PLATE THS.1	1	23-AUG-80	12	07
PLATE PTS.1	9	23-AUG-80	12	19
PLATE ELT.1	18	23-AUG-80	12	07
PLATE LIN.1	10	23-AUG-80	12	07
PLATE GRD.1	7	23-AUG-80	12	07
PLATE PAR.1	1	23-AUG-80	12	15
PLATE LDS.1	7	23-AUG-80	12	20
PLATE ELO.1	14	23-AUG-80	12	20
PLATE SDY.1	1	23-AUG-80	12	27
PLATE STF.1	23	23-AUG-80	12	28
PLATE LDI.1	6	23-AUG-80	12	30
PLATE DNI.1	6	23-AUG-80	12	30
PLATE DNS.1	5	23-AUG-80	12	30
PLATE STR.1	7	23-AUG-80	12	31

TOTAL OF 117 /160. BLOCKS IN 16 FILES

Figure 4 - Listing of Files Created by GIFTS JOB PLATE

```

MAIN      ROOT MAIN-(A,B,C1-C2,D,E,F,G,H,I,J,K,L,M)
ML1B     FCTR BULKM/LB MAIN DELINE GENCLC LOCL-ML1B-CLB
A         FCTR CIFTL1B/LB LINPN DEFIN TWAIT DFIL
B         FCTR *BULKM/LB INITBM STOPBM-CIFTL1B/LB
INE-CLB  FCTR *BULKM/LB GENLNS CARC CMLPN GENLE PARAM2 PARAM3 RSTCDS SL
C1        FCTR *BULKM/LB CENCDS GENSE3 GENSE4 CLOB CRDC03 CRDC04 CRIDT CR
103       FCTR *BULKM/LB CRID4 INGPT LOCC MULC OUTCPT PCRID-CIFTL1B/LB
C2        FCTR *BULKM/LB SCALE PLOTBM LBLPLC-CIFTL1B/LB
D         FCTR *BULKM/LB COMBM HELP SWITCH-CIFTL1B/LB
E         FCTR *BULKM/LB ARBLIN LINI MERCLN THSS LCELTY MATL STANDM BMPLP
R-CLB    FCTR *BULKM/LB ACDPTR DCDPTR CRIDT1 CRID31 CRID41-CIFTL1B/LB
C         FCTR *BULKM/LB COMPOS CPTIME DCMPL DELCAL DCDPTR DLETBM CLASSB-
H         CIFTL1B/LB
I         FCTR *BULKM/LB ERRBM INFBM-CIFTL1B/LB
J         FCTR *BULKM/LB BEMSEC-CIFTL1B/LB
K         FCTR *BULKM/LB GENKPT KPOINT KCARC K2PARM K3PARM KSLINE-CIFTL1B
/LB       FCTR *BULKM/LB FNCTN PROJECT PRJECT-CIFTL1B/LB
L         FCTR *BULKM/LB POLYC-CLB-*(M1,M2)
M         FCTR *BULKM/LB INPOLY-CIFTL1B/LB
M1        FCTR *BULKM/LB CALPOL-CIFTL1B/LB
M2        FCTR CIFTL1B/LB
CLB       END

```

Figure 5 - Listing of BULKM ODL

BRO 11: BUILDING GIFTS

TKB @STRESS
TIME
TKB @EDITLB
TIME
TKB @SAVEK
TIME
TKB @RESIDU
TIME
TKB @BULKLB
TIME
TKB @STIFF
TIME
TKB @BULKM
TIME
TKB @DEFL
TIME
TKB @RESULT
TIME
TKB @BULKF
TIME
TKB @DECOM
TIME
TKB @EDITM
TIME
TKB @AUTOL
TIME
TKB @DEFCS
TIME
TKB @LOCAL
TIME
TKB @SUBS
TIME
TKB @TRAN1
TIME
TKB @TRANS
TIME
TKB @OPTIM
TIME
TKB @PRINT
TIME
TKB @TRAN2
TIME
TKB @REDCS
TIME
BRO 11: DONE BUILDING GIFTS

Figure 6 Listing of CIFTSS.CMD

Figure 7 -Listing of Files Needed to Execute CIFTSS.CMD

CIFTLB OLB.1
GLIB2 OLB.1
OPTIM OLB.1
DECOM OLB.1
BULK1 OLB.1
SUBS OLB.1
DEFCS OLB.1
LOCAL OLB.1
TRANS OLB.1
STRESS OLB.1
DEFL OLB.1
STIFF OLB.1
REDCS OLB.1
EDITLB OLB.1
EDITM OLB.1
RESULT OLB.1
BULKM OLB.1
DECOM OLB.53
OPTIM OLB.17
BULKM OLB.52
BULKLB OLB.56
DEFL OLB.55
EDITM OLB.52
LOCAL OLB.65
SUBS OLB.57
DEFCS OLB.65
TRANS OLB.61
STRESS OLB.55
STIFF OLB.52
REDCS OLB.62
RESULT OLB.64
EDITLB OLB.56

STIFF CHO.11
SUBS CHO.11
TRAN1 CHO.11
TRANS CHO.11
OPTIM CHO.11
STRESS CHO.11
EDITLB CHO.15
SAVEK CHO.11
PRINT CHO.11
RESIDU CHO.11
TRAN2 CHO.11
REDCS CHO.11
CIFTSS CHO.11
BULKM CHO.26
BULKLB CHO.13
DEFL CHO.11
RESULT CHO.15
BULKF CHO.28
EDITM CHO.12
AUTOL CHO.14
DECOM CHO.11
DEFCS CHO.12
LOCAL CHO.11

APPENDIX A

DESCRIPTION OF GIFTS MODULES¹²

MODEL GENERATION AND EDITING

BULKM

BULKM is an automated three dimensional plate and shell model generator. It is suitable for large continuous structure that can be easily modeled by repetitious generation of points and elements.

EDITM

EDITM is designed to update and correct BULKM models, although it can be used to generate simple models and ones too complex for BULKM.

DEPCS

DEPCS accepts information regarding external and dependent boundary nodes in a constrained substructure.

BULK3¹³

BULK3 is a three dimensional solid model generator. One may ask for the display of the edges, and may add and display selected point and element slices.

¹²The descriptions here are taken from the "GIFTS User's Manual."

¹³BULK3, as of the date of this writing, is not yet implemented on the PDP-11. This is primarily due to its size.

LOAD AND BOUNDARY CONDITION
GENERATION, DISPLAY AND EDITING

BULKF

BULKF is intended to allow only those freedoms which a model can support, thereby relieving the user of the necessity of suppressing all superfluous freedoms by hand.

BULKLB

BULKLB is a bulk load and boundary condition generator designed to apply load to models generated with BULKM. It may be used to apply distributed line and surface loads and masses, prescribed displacements along lines and surfaces and inertial loads. Temperatures may also be applied to lines and surfaces.

EDITLB

EDITLB is a display and edit routine intended to provide local modification capability to loads and boundary conditions applied by BULKLB. It may also be used to generate simple loading on models, or loading on models not generated with BULKM. Temperatures may also be applied to elements. After DATA has been run, the thermal and combined loads may be examined.

LOADS¹⁴

LOADS is a load and boundary condition generator for solid models. Loads may be distributed on lines or

¹⁴LOADS, as of the date of this writing, is not yet implemented on the PDP-11. This is primarily due to size.

surfaces. Loads and boundary conditions may be displayed on point slices.

GENERAL PURPOSE COMPUTATIONAL AND RESULT DISPLAY MODULES

OPTIM

OPTIM is a band width optimization program. Although GIFTS is designed to handle problems without size or band-width restrictions, it is very important that the problem be optimized before the solution proceeds. Experience has shown that run times can be reduced by a factor of two to ten if the procedure is used. OPTIM may be called several times in a row, until the best node numbering scheme has been achieved.

STIFF

STIFF performs computation of the stiffness matrices and assembles them into the master stiffness matrix.

DECOM

DECOM introduces kinematic boundary conditions, and decomposes that stiffness matrix by the Cholesky method.

DEFL

DEFL computes the deflections from the current loading conditions and the decomposed stiffness matrix. If temperatures are present, thermal forces will be calculated and added to the current applied loads before solution.

STRESS

STRESS computes the element stresses based on the current deflections.

RESULT

RESULT displays deflections and stresses. It has many options that may be used, at the discretion of the user, to transform the results for optimum comprehension.

THE GIFTS NATURAL VIBRATION PACKAGE

AUTOL

AUTOL is ordinarily used to generate starting loads for the subspace iteration to compute natural modes of vibration.

SUBS

SUBS performs a single subspace iteration to determine the model's natural modes. It must be repeated as many times as necessary to obtain convergence to the desired extent.

THE GIFTS TRANSIENT RESPONSE PACKAGE (DIRECT INTEGRATION)

TRAN1

TRAN1 is to be run on a transient response model immediately after stiffness assembly. It is used to specify the time step to be used in the integration process.

TRAN2

TRAN2 is run after TRAN1 and DECOM. It computes the displacement matrix for time T.

TRANS

TRANS maintains and plots histograms of the displacements of up to four different freedoms.

GIFTS CONSTRAINED SUBSTRUCTURING PACKAGE

REDCS

Before a COSUB module may be used in a master analysis run, it must be preceded by program REDCS to form a reduced stiffness matrix and a reduced load matrix (if there are any loads associated with the COSUB).

APPENDIX E

LIST OF GIFTS MANUALS¹⁵

GIFTS USER'S REFERENCE MANUAL

"Contains complete and detailed description of all GIFTS commands and computational procedures. It is meant as a source of information for the experienced user."

GIFTS SYSTEMS MANUAL

"Contains detailed information on the code, data base and program structure. Useful for those undertaking program conversion or enhancement."

Though there is a great deal of detail concerning the UDB and program structure (for the ECLIPSE Computer), there is really insufficient information to get started in a "program conversion or enhancement." There are several terms and acronyms which are undefined in the description where knowledge of the other manuals are essential for understanding.

GIFTS PRIMER

". . . useful to new users, and to exercise the system on a new installation, or check out a new version of the program on an existing installation . . . Tutorial . . . Solved Examples."

This manual is excellent for the intended purposes. Anyone seriously intending to use the system should spend several hours with this manual and the computer.

¹⁵Remarks in quotation marks are taken directly from pages SPRIN-1-3 & 4 from the GIFTS Primer.

GIFTS INSTALLATION MANUAL

"Designed to help those attempting to install the program on their own system. Describes implementation and test procedures."

This manual, as of this writing, is not implemented. It is hoped that with respect to the PDP-11, this thesis provides some of the information needed.

GIFTS THEORETICAL MANUAL

"Contains mathematical fundamentals and algorithms underlying mesh generation, element characteristics and solution procedures. Of use to those wishing to assess the properties of the mathematical model used, or modify the program."

GIFTS MODELLING GUIDE

"Aimed at the program user. Discusses practical aspects of finite element modelling in general and pays particular attention to elements and procedures implemented in the GIFTS system."

Not implemented as of this writing.

GIFTS POCKET MANUAL

"A handy pocket-size reference manual containing complete, but terse, summary of information in the GIFTS Users Reference Manual. Used mainly as a quick reference manual to be used while working on a terminal by the experienced user."

Emphasize experienced!

APPENDIX C

LISTING OF PROGRAM: FILSOR

```

C*****FILE SORTER*****
C*****WRITTEN BY JOHN T. SHELDON*****
C*****LAST UPDATED 8/25/80 BY JTS*****
C
C      THIS PROGRAM IS A FILE SORTER.  IT WAS SPECIFICALLY
C      WRITTEN WITH THE "GIFTS" SYSTEM IN MIND.  THE GIFTS
C      SOURCE LISTINGS HAVE THE FOLLOWING CHARACTERISTICS:
C
C      1) THERE ARE NO BLOCK DATA SUBROUTINES;
C      2) SOME OF THE CONCATENATED LISTINGS START
C          WITH A MAIN PROGRAM;
C      3) FIVE OF THE FORTRAN LISTINGS INCLUDE ONLY
C          SUBROUTINES OR FUNCTIONS(IE NO MAIN
C          PROGRAMS);
C      4) IN ALL CASES, THE PROGRAM, SUBROUTINES AND
C          FUNCTIONS(PSF) WILL HAVE TO BE COMPILED;
C      5) IN SOME CASES, ENTIRE SYSTEMS OF SORTED
C          SUBROUTINES WILL HAVE TO BE COMPILED
C          WITH THE "/TR:NONE" SWITCH IN USE;
C      6) IN ALL CASES, THE SORTED PSF'S WILL HAVE
C          TO BE PUT IN A LIBRARY.
C      7) THE COMMENT STATEMENTS PRECEDING THE FIRST
C          EXECUTABLE STATEMENT ARE DISCARDED;
C      8) THE INPUT FILE IS UNAFFECTED BY THIS PROGRAM;
C      9) THE "END" STATEMENT BEGINS IN COLUMN 7
C
C      BYTE YES,NO,ANS,ANANS(40),LINE(72),OBLANK
C      BYTE F,E,NN,C,S,DD,SFLAG

```

```

FIL00030
FIL00040
FIL00050
FIL00060
FIL00070
FIL00080
FIL00090
FIL00100
FIL00110
FIL00120
FIL00130
FIL00140
FIL00150
FIL00160
FIL00170
FIL00180
FIL00190
FIL00200
FIL00210
FIL00220
FIL00230
FIL00240
FIL00250
FIL00260
FIL00270
FIL00280
FIL00290
FIL00300
FIL00310
FIL00320
FIL00330
FIL00340
FIL00350
FIL00360
FIL00370
FIL00380
FIL00390
FIL00400
FIL00410
FIL00420
FIL00430

```



```

IF(ENDIT.EQ..TRUE.)GO TO 25
CALL RDLN(LINE)
LOOK FOR "E" IN COLUMN 7 AND "N" IN COLUMN 8
ENDIT=(LINE(7).EQ.E).AND.(LINE(8).EQ.N)
MAKE OTHER CHECKS TO ENSURE THIS IS AN END STATEMENT
IF(.NOT.(ENDIT.AND.(LINE(9).EQ.DD.AND.LINE(10).EQ.32)))
  IF(ENIT=.FALSE.
  IF(LINE(1).EQ.C)ENDIT=.FALSE.
  N=0
  DO 21 I=1,72
  21 IF(LINE(I).NE.OBLANK)N=I
  GO TO 20
  DONE WITH THIS OUTPUT
  25 CLOSE(UNIT=2,DISP='SAVE')
  GO TO 15
  100 FORMAT(20X,' ***FILE SORTER***,/)
  101 FORMAT(80A1)
  104 FORMAT(',$TYPE IN NAME OF FILE INCLUDING EXTENSION:')
  105 FORMAT(1X,80A1)
  106 FORMAT(',$"/TR:NONE" SWITCH DESIRED FOR COMPILE?(Y OR N):')
  END
  SUBROUTINE CMDFIL(FILNAM)
  *****
  *****WRITTEN BY JOHN T. SHELDON*****
  *****
  *** LAST UPDATED ON 8/25/80 BY JTS
  *****
  *****
  THIS SUBROUTINE IS PART OF THE FILSOR PACKAGE
  IT TAKES THE FILNAME(FILNAM) AND DETERMINES THE
  LIB.CMD AND STUFF.CMD INPUTS.
  LIB.CMD IS A FILE OF STATEMENTS WHICH ARE
  USED ALONG WITH THE F4P COMPILER ON THE
  POP11. THE OUTPUT LINES ARE OF THE FORM:
  /TR:NONE'
  THE /CO:20 SWITCH HAS BEEN INSERTED AS
  A FEW OF THE SUBROUTINES WILL HAVE MORE
  THAN THE DEFAULT CONTINUATION LINES.
  THE /TR:NONE SWITCH IS AN OPTION WHICH
  IS USED IF SPACE IS AT A PREMIUM(AS IN
  THE RESULT AND BULKLB MODULES OF GIFTS.

```



```

FIL01400
FIL01410
FIL01420
FIL01430
FIL01440
FIL01450
FIL01460
FIL01470
FIL01480
FIL01490
FIL01500
FIL01510
FIL01520
FIL01530
FIL01540
FIL01550
FIL01560
FIL01570
FIL01580
FIL01590
FIL01600
FIL01610
FIL01620
FIL01630
FIL01640
FIL01650
FIL01660
FIL01670
FIL01680
FIL01690
FIL01700
FIL01710
FIL01720
FIL01730
FIL01740
FIL01750
FIL01760
FIL01770
FIL01780
FIL01790
FIL01800
FIL01810
FIL01820
FIL01830
FIL01840
FIL01850
FIL01860
FIL01870

```

STUFF.CMD IS A FILE OF INDIVIDUAL "LBR"
COMMANDS WHICH "STUFF" THE COMPILED
OBJECT MODULES IN A LIBRARY CALLED
(ARBITRARILY): LI.OLB

THE ABOVE TWO FILES ARE EXECUTED IN THE FOLLOWING
ORDER AND WITH THE SAME SYNTAX:

```

@F4PLIB
@STUFF

```

ERRORS DURING COMPILE WOULD BE PRINTED. OTHERWISE
NO OUTPUT SHOULD BE EXPECTED FROM THE FIRST LINE.
STUFF, ON THE OTHERHAND, WILL PRINT EACH COMMAND
LINE.

```

BYTE ISLASH,IEQ,SFLAG
BYTE FILNAM(40),OBLANK,LIBNAM(2),IDOT,LOUTPT(40),MOUTPT(40)
DIMENSION LOUTP(20),MDUP(5),LLOUP(7)
COMMON SFLAG
EQUIVALENCE (LOUTPT(1),LOUP(1)),(MOUTPT(1),MDUP(1))
DATA IEQ/1H=/
DATA LLOUP(1),LOUP(2),MDUP(1),MDUP(2)/2H,2HLB,2HR /
1 IFLAG,LIBNAM(1),LIBNAM(2),OBLANK/O,1HL,1H /
2 IDOT,MDUP(3),MDUP(4),MDUP(5)
3 LLOUP(1),LLOUP(2),LLOUP(3)/2H/C,2HO:,2H2O/
4 LLOUP(4),LLOUP(5),LLOUP(6)/2H/T,2HR:,2HNO/
5 LLOUP(7)/2HNE/
SFLAG = 1 INDICATES /TR:NONE SWITCH IS TO BE LEFT IN
SFLAG = 0 WILL CAUSE THE ARRAY HOLDING THIS EXPRESSION
TO BE ZEROED
IF(SFLAG.EQ.1)GO TO 5
DO 3 I=4,7
3 LLOUP(I)=0
SFLAG=0
CHECK TO SEE IF FIRST PASS THROUGH SUBROUTINE
IF IT IS, MUST OPEN FILES
5 IF(IFLAG.EQ.1)GO TO 10
OPEN COMMAND FILES
LU=3 "STUFF.CMD" FILE
1 OPEN(UNIT=3,NAME='STUFF.CMD',TYPE='UNKNOWN',
ACCESS='APPEND',DISP='SAVE')

```

CCCCCCCCCCCCCCCCCCCCCCCCCCCC

CC

CC

CC

```

FIL01880
FIL01890
FIL01900
FIL01910
FIL01920
FIL01930
FIL01940
FIL01950
FIL01960
FIL01970
FIL01980
FIL01990
FIL02000
FIL02010
FIL02020
FIL02030
FIL02040
FIL02050
FIL02060
FIL02070
FIL02080
FIL02090
FIL02100
FIL02110
FIL02120
FIL02130
FIL02140
FIL02150
FIL02160
FIL02170
FIL02180
FIL02190
FIL02200
FIL02210
FIL02220
FIL02230
FIL02240
FIL02250
FIL02260
FIL02270
FIL02280
FIL02290
FIL02300
FIL02310
FIL02320
FIL02330
FIL02340
FIL02350

```

```

C LU=4 "LIB.CMD" FILE
  OPEN(UNIT=4,NAME=LIB.CMD,TYPE='UNKNOWN',
  1 ACCESS='APPEND',DISP='SAVE')
  IFLAG=1
  10 DO 15 I=1,16
    IF(FILNAM(I).EQ.OBLANK-OR.FILNAM(I).EQ.IDOT)GO TO 16
  C N IS THE NUMBER OF CHARACTERS IN THE NAME OF THE PSF
    N=I
  15 CONTINUE
  C M,N,---
  C OF CHARACTERS IN "FILNAM"
  16 M=N
  C BUILD LIB.CMD FILE INPUT
    N=N+4
    DO 20 I=5,N
      20 LOUPT(I)=FILNAM(I-4)
      LOUPT(N)=IEQ
      DO 30 I=N+1,N+4
        30 LOUPT(I)=FILNAM(I-M-5)
      DO 35 I=N+1,26
        35 LOUPT(I)=OBLANK
      DO 36 I=14,20
        36 LDUP(I)=LDUP(I-13)
      WRITE(4,100)LOUPT
  C BUILD STJFF.CMD FILE INPUT
    DO 40 I=1,M+10
      40 MOUPT(I)=FILNAM(I-10)
    DO 45 I=M+11,40
      45 MOUPT(I)=OBLANK
    WRITE(3,100)MOUPT
    RETURN
  100 FORMAT(80A1)
  END
  SUBROUTINE NAMEFL(LINE,ANANS)
  C *****
  C *****WRITTEN BY JOHN T. SHELDON*****
  C *****
  C *** LAST UPDATED ON 8/25/80 BY JTS
  C *****
  C *****
  C THIS SUBROUTINE IS A PART OF THE FILSOR PACKAGE.
  C ITS PURPOSE IS TO OBTAIN THE NAME OF THE "OUTFILE"
  C *****

```

```

C C C C C
      BE IT A MAIN PROGRAM, SUBROUTINE OR FUNCTION.

      A LINE OF DATA IS ENTERED(LINE) AND THE PSF IS
      RETURNED(ANANS)
      BYTE LINE(72),ANANS(40),S(12),F(8),OBLANK,PAREN
      BYTE IDOT,FF,TT,NN,SFLAG
      COMMON SFLAG
      DATA S(1),S(2),S(3),S(4),S(5) /IHS,IHU,IHB,IHR,IHO/
      S(6),S(7),S(8),S(9),S(10) /IHT,IHI,IHN,IHE/
      F(1),F(2),F(3),F(4),F(5) /IHF,IHU,IHN,IHC,IHT/
      F(6),F(7),F(8),OBLANK,PAREN/IHI,IHO,IHN,IH,IH(/
      FF,TT,NN,IDOT,OFLAG /IHF,IHT,IHN,IH.,O/
      ZERO ANANS
      IF(OFLAG.EQ.0)30 TO 11
      DO 10 I=1,40
      10 ANANS(I)=OBLANK
      11 CONTINUE
      C LOOK FOR "SUBROUTINE" OR "FUNCTION"
      DO 15 I=7,50
      N=I
      C LOOKING FOR LETTER "S"
      IF(LINE(I).EQ.S(1))GO TO 20
      C DIDN'T FIND S, HOW ABOUT AN "F"
      15 IF(LINE(I).EQ.F(1))GO TO 30
      C THIS MUST BE A MAIN PROGRAM SINCE THERE IS NO LETTER
      "S" OR "F" IN THE FIRST EXECUTABLE LINE.
      16 CONTINUE
      C THIS MEANS THAT "ANSWER"(ANANS) CONTAINS
      C RIGHT FILE NAME BUT WRONG EXTENSION
      C (THIS IS TRUE SINCE THE MAIN PROGRAM IN THE GIFTS
      C LISTINGS ARE ALWAYS THE FIRST IN THE PACKAGE.
      C THEREFORE, TO HAVE GOTTEN TO THIS POINT, WE'RE
      C LOOKING FOR A MAIN PROGRAM. ANANS HASN'T BEEN
      C CHANGED SINCE IT WAS USED TO GET THE NAME OF
      C THE INPT FILE.
      DO 17 I=1,6
      II=I
      IF(ANANS(I).EQ.IDOT)GO TO 18
      17 CONTINUE
      II=II+1
      18 ANANS(II+1)=FF
      ANANS(II+2)=TT
      ANANS(II+3)=NN
      ANANS(40)=0
      RETURN
      C CHECK IF A "SUBROUTINE". IF NOT THEN MUST

```

```

FIL02360
FIL02370
FIL02380
FIL02390
FIL02400
FIL02410
FIL02420
FIL02430
FIL02440
FIL02450
FIL02460
FIL02470
FIL02480
FIL02490
FIL02500
FIL02510
FIL02520
FIL02530
FIL02540
FIL02550
FIL02560
FIL02570
FIL02580
FIL02590
FIL02600
FIL02610
FIL02620
FIL02630
FIL02640
FIL02650
FIL02660
FIL02670
FIL02680
FIL02690
FIL02700
FIL02710
FIL02720
FIL02730
FIL02740
FIL02750
FIL02760
FIL02770
FIL02780
FIL02790
FIL02800
FIL02810
FIL02820
FIL02830

```

```

C      BE THE BEGINNING OF THE MAIN PROGRAM
20  IDIF=N-1
21  IF(LINE(I).NE.S(I-IDIF))GO TO 16
C      MUST BE A SUBROUTINE
C      FIRST ZERO ANANS
22  DO 22 I=1,40
23  ANANS(I)=0
24  N=N+10
25  IF(LINE(I).NE.DBLANK) GO TO 24
26  N=I
27  IDIF=N-1
28  DO 25 I=N,N+6
29  IF(LINE(I).EQ.DBLANK.OR.LINE(I).EQ.PAREN)GO TO 26
30  ANANS(I-IDIF)=LINE(I)
31  ANANS(I-IDIF+1)=FF
32  ANANS(I-IDIF+2)=TT
33  ANANS(I-IDIF+3)=NN
34  ANANS(40)=0
35  RETURN
36  CHECK IF A "FUNCTION". IF NOT, MUST THE BEGINNING OF A PROGRAM
C
C      30  IDIF=N-1
C      31  DO 31 I=N,N+7
C      32  IF(LINE(I).NE.F(I-IDIF))GO TO 16
C      33  MUST BE A FUNCTION
C      34  FIRST ZERO ANANS
C      35  DO 32 I=1,40
C      36  ANANS(I)=0
C      37  N=N+8
C      38  DO 33 I=N,N+5
C      39  IF(LINE(I).NE.DBLANK)GO TO 34
C      40  N=I
C      41  IDIF=N-1
C      42  DO 35 I=N,N+6
C      43  IF(LINE(I).EQ.DBLANK.OR.LINE(I).EQ.PAREN)GO TO 26
C      44  ANANS(I-IDIF)=LINE(I)
C      45  GO TO 26
C      102  FORMAT(80A1)
C      END
C      SUBROUTINE ROLINE(LINE)
C      *****
C      *****WRITTEN BY JOHN T. SHELDON*****
C      *** LAST UPDATED ON 8/25/80 BY JTS

```

```

FIL02840
FIL02850
FIL02860
FIL02870
FIL02880
FIL02890
FIL02900
FIL02910
FIL02920
FIL02930
FIL02940
FIL02950
FIL02960
FIL02970
FIL02980
FIL02990
FIL03000
FIL03010
FIL03020
FIL03030
FIL03040
FIL03050
FIL03060
FIL03070
FIL03080
FIL03090
FIL03100
FIL03110
FIL03120
FIL03130
FIL03140
FIL03150
FIL03160
FIL03170
FIL03180
FIL03190
FIL03200
FIL03210
FIL03220
FIL03230
FIL03240
FIL03250
FIL03260
FIL03270
FIL03280
FIL03290
FIL03300
FIL03310

```

FIL03320
 FIL03330
 FIL03340
 FIL03350
 FIL03360
 FIL03370
 FIL03380
 FIL03390
 FIL03400
 FIL03410
 FIL03420
 FIL03430
 FIL03440
 FIL03450
 FIL03460
 FIL03470
 FIL03480
 FIL03490
 FIL03500

```

C*****
C THIS SUBROUTINE IS PART OF THE FILSOR PACKAGE
C*****
C THE PURPOSE OF THIS SUBROUTINE IS TO READ A
C LINE FROM THE INPUT FILE. IF AN "EOF" IS
C REACHED, ALL OPEN FILES ARE CLOSED AND THE
C FILSOR PROGRAM IS STOPPED HERE.
C*****
      BYTE LINE(72)
      READ(1,100,END=10)LINE
      RETURN
10  DO 20 I=1,4
20  CLOSE(UNIT=I)
      STOP
100 FORMAT(80A1)
      END
  
```

APPENDIX D

SAMPLE SESSION WITH FIELSOL

The following is a listing from an actual run with FIELSOL. It has been annotated to indicate what actually is going on and the reasons for the various steps.

The BUILDL.CMD file executes this entire process "automatically" with the exception that the FIELSOL2 version of FIELSOL is needed as well as the SEVERE.CSK file (which generates the answers to the FIELSOL questions asked below). BUILDL, of course, also reads the necessary files from magnetic tape.

>PIP/LI

DIRECTORY DP3 [160,53] (1)
30-AUG-80 15:46

OPTIM.OOL,47	1		30-AUG-80 15:33
FILSOR.TSK,2	51	C	30-AUG-80 15:33
OPTIM.NEW,1	53		30-AUG-80 15:33
OPTIM.CMD,10	1		30-AUG-80 15:33
GIFTLIB.OLB,1	592	C	30-AUG-80 15:45

TOTAL OF 698 /698. BLOCKS IN 5. FILES

>RUN FILSOR

FILE SORTER

"/TR: NONE" SWITCH DESIRED FOR COMPILE?(Y OR N) N
TYPE IN NAME OF FILE INCLUDING EXTENSION OPTIM.NEW
TT36 -- STOP

>F4P OLIB (3)

>PIP *.OBJ/LI (4)

DIRECTORY DP3 [160,53]
30-AUG-80 15:48

OPTIM.OBJ,1	1	30-AUG-80 15:46
BAND.OBJ,1	6	30-AUG-80 15:47
INOPT.OBJ,1	5	30-AUG-80 15:47
OPT.OBJ,1	10	30-AUG-80 15:47
SWAP.OBJ,1	3	30-AUG-80 15:47
TEROPT.OBJ,1	14	30-AUG-80 15:47

TOTAL OF 39 /50. BLOCKS IN 6. FILES (5)

>LBR LI/CR.39.6.6.OBJ (6)

>ESTUFF (7)

>LBR LI/IN-OPTIM

>LBR LI/IN-BAND

>LBR LI/IN-INOPT

>LBR LI/IN-OPT

>LBR LI/IN-SWAP

>LBR LI/IN-TEROPT

>E <EOF>

>PIP OPTIM.OLB-LI.OLB/RE (8)

>TKB EOPTIM (9)

>PIP/LI

(10)

DIRECTORY DP3 [160,53]
30-AUG-80 15:51

STUFF.CMD,1	1		30-AUG-80 15:46
OPTIM.OOL,47	1		30-AUG-80 15:33
LIB.CMD,1	1		30-AUG-80 15:46
FILSOR.TSK,2	51	C	30-AUG-80 15:33
OPTIM.NEW,1	53		30-AUG-80 15:33
OPTIM.FTN,1	2		30-AUG-80 15:46
OPTIM.CMD,10	1		30-AUG-80 15:33
BAND.FTN,1	7		30-AUG-80 15:46
INOPT.FTN,1	7		30-AUG-80 15:46
OPT.FTN,1	18		30-AUG-80 15:46
SWAP.FTN,1	4		30-AUG-80 15:46
TEROPT.FTN,1	14		30-AUG-80 15:46
OPTIM.OBJ,1	1		30-AUG-80 15:46
BAND.OBJ,1	6		30-AUG-80 15:47
INOPT.OBJ,1	5		30-AUG-80 15:47
OPT.OBJ,1	10		30-AUG-80 15:47
SWAP.OBJ,1	3		30-AUG-80 15:47
TEROPT.OBJ,1	14		30-AUG-80 15:47
GIFTLIB.OLB,1	592	C	30-AUG-80 15:45
OPTIM.OLB,1	40		30-AUG-80 15:48
OPTIM.TSK,1	209	C	30-AUG-80 15:49
OPTIM.STB,1	6		30-AUG-80 15:51

TOTAL OF 1046 /1086 BLOCKS IN 22 FILES

>PIP *.FTN,*/DE
>PIP *.OBJ,*/DE
>PIP *.CMD,*/DE
>PIP *.OOL,*/DE
>PIP *.OLB,*/DE
>PIP FILSOR.TSK,*/DE
>PIP OPTIM.NEW,*/DE
>PIP/LI

(11)

(12)

DIRECTORY DP3 [160,53]
30-AUG-80 15:52

OPTIM.TSK,1	209	C	30-AUG-80 15:49
OPTIM.STB,1	6		30-AUG-80 15:51

TOTAL OF 215 /219 BLOCKS IN 2 FILES

>

(1) The first thing done is a "PIP/II" which lists all files in the directory. In this case, the response indicates that we're in directory 160,53. The files listed are all the files needed to build OPTIM. If RESULT or BULKIE were being built, then GLIB2 would replace GIPLIB as the GIPIS "System" library. Also, as a means of differentiating the BULKIE and RESULT module libraries (see section IV.D) these libraries are arbitrarily referred to, in the command files, as BULK1 and RESULT1, respectively.

(2) PILESOR is executed. It responds by asking two questions before proceeding.

(3) The sorted program/subroutines are compiled separately using the command file: LIB:PED (which was generated by PILESOR (see listing in item (10) below)). If an error were generated during compile, the compiler would indicate which subroutine had the error(s). This would not, however, inhibit the further completion of compilation.

(4) This is a listing of the "Object" files generated by the P4P @LIB command.

(5) Note that 39 blocks in six files were generated. These numbers are critical in that they are used to create a library in the next step.

(6) Using the "LBR" utility, a library "L1.OLB" is created. The decimal points are parts of the syntax in this command as the omission of them indicates octal numbers. The name

"L1" is used only because the "SYSTEM.L1" file, built by MIESOP is looking, arbitrarily, for a object library called L1.

(7) Library L1.OLE is "stuffed" In the case of this command file, each command is subsequently listed until and <EOF> is encountered. In this example, six object modules have been inserted into library L1.OLE.

(8) Using PIP, the library L1.OLE is renamed: OPTIM.OLE. This is the library name which will be used by OPTIM.OHD when taskbuilding OPTIM.

(9) OPTIM is finally "taskbuilt."

(10) A listing of the files which have been generated while building the executable module, OPTIM.TSK, and the symbol table file, OPTIM.STB. Note that the sum of the space taken up by the files is over 1000 blocks.

(11) Housekeeping. Those files unnecessary to the execution of the OPTIM module are deleted by the seven PIP directives shown.

(12) A listing of what remains: the two files necessary to execute optimization.

APPENDIX C

LISTING OF BUFILE.CMD

```

TYPE
.ASK QUES ARE THE TWO TAPES MOUNTED
.IFF QUES .GOTO 200
.ASK QUES HAVE YOU DONE A "PID/END"
.IFF QUES .GOTO 200
.ASK QUES ARE THERE AT LEAST 9K BLOCKS AVAILABLE
.IFF QUES .GOTO 200
.ASK QUES THIS IS GOING TO TAKE ABOUT 6 HOURS. READY
.IFF QUES .GOTO 200
FLX /PC=MT1: 20,1 FILE02.TSK/00
FLX /PC=MT1: 20,1 STUFF.TSK/00
PID *.*=FILE02.TSK/00
PID *.*=STUFF.TSK/00
PID *.TSK/00
FLX /PC=MT1: 20,1 *.000/00
FLX /PC=MT1: 20,1 *.001/00
FLX /PC=MT: 20,1 11001.NCH/00
FLX /PC=MT: 20,1 11002.NCH/00
FLX /PC=MT: 20,1 11003.NCH/00
FLX /PC=MT: 20,1 11004.NCH/00
FLX /PC=MT: 20,1 11005.PCH/00
FLX /PC=MT: 20,1 0011.MAC/00
FLX /PC=MT: 20,1 100001.MAC/00

```

THIS PAGE IS BEST QUALITY REPRODUCTION
FROM COPY FORWARDED TO NSA

PIP STUFF
 RUN FILS02
 RUN FILS02
 RUN FILS02
 RUN FILS02
 RUN FILS02
 L30 L1/00:630.:304.:304.:00J
 F40 0L10
 STUFF
 PIP CIFT110.010=L1.010/00
 PIP *.FT0;*/00
 PIP *.000;*/00
 PIP L10.000;*/00
 PIP STUFF.000;*/00
 TIME
 RUN FILS02
 RUN FILS02
 RUN FILS02
 RUN FILS02
 RUN FILS02
 PIP *.000;*/00
 PIP *.000;*/00
 L30 L1/00:500.:304.:304.:00J
 F40 0L10
 STUFF
 PIP CL102.010=L1.010/00
 PAC 0010=0010
 PAC 10000=10000
 PIP *.PAC;*/00
 L30 CIFT110/00=0010,10000
 L30 CL102/00=0010,10000
 PIP *.FT0;*/00
 PIP *.000;*/00
 PIP L10.000;*/00

THIS PAGE IS BEST QUALITY REPRODUCTION
 FROM COPY PROVIDED TO NSA

PIP STUFF.CMP;*/*
 FLX /PS=PT: 20,1 STRESS.NEU/DO
 TIME
 RUN FILSR2
 L37 LI/CP:200.:100.:100.:08J
 F4P QLIB
 QSTUFF
 PIP STRESS.OIB=L1.OIB/RE
 PIP *.FTI;*/*
 PIP *.OQJ;*/*
 PIP LIB.CMP;*/*
 PIP STUFF.CMP;*/*
 PIP *.NEU;*/*
 FLX /PS=PT: 20,1 EDITL.NEU/DO

TIME
 RUN FILSR2
 L37 LI/CP:100.:100.:100.:05J
 F4P QLIB
 QSTUFF
 PIP EDITL.OIB=L1.OIB/RE
 PIP *.FTI;*/*
 PIP *.OQJ;*/*
 PIP LIB.CMP;*/*
 PIP STUFF.CMP;*/*
 PIP *.NEU;*/*
 FLX /PS=PT: 20,1 FULLIB.NEU/DO

TIME
 RUN FILSR2
 L37 LI/CP:240.:100.:100.:08J
 F4P QLIB
 QSTUFF
 PIP 344L1.OIB=L1.OIB/RE
 PIP *.FTI;*/*
 PIP *.OQJ;*/*

THIS PAGE IS BEST QUALITY PRINTING
 FROM COPY FROM LISTED TO ME

```

PIP LIB.CMD;*/DE
PIP STUFF.CMD;*/DE
PIP *.NEW;*/DE
FLX /RS=RT: 20,1 STUFF.NEW/DO
TIME
RUN FILSD2
LSP LI/CR:170.:100.:100.:00J
F4P QLIB
QSTUFF
PIP STUFF.OLB=L1.013/RS
PIP *.FTN;*/DE
PIP *.OBJ;*/DE
PIP LIB.CMD;*/DE
PIP STUFF.CMD;*/DE
PIP *.NEW;*/DE
FLX /RS=RT: 20,1 BULB.NEW/DO
TIME
RUN FILSD2
LSP LI/CR:450.:100.:100.:00J
F4P QLIB
QSTUFF
PIP BULB.OLB=L1.013/RS
PIP *.FTN;*/DE
PIP *.OBJ;*/DE
PIP LIB.CMD;*/DE
PIP STUFF.CMD;*/DE
PIP *.NEW;*/DE
FLX /RS=RT: 20,1 BULB.NEW/DO
TIME
RUN FILSD2
LSP LI/CR:110.:100.:100.:00J
F4P QLIB
QSTUFF
PIP BULB.OLB=L1.013/RS

```

THIS PAGE IS BEST QUALITY PRINTING
FROM COPY FURNISHED TO HQ

```
PIP *.OBJ;*/DE
PIP *.FTN;*/DE
PIP LIB.CMD;*/DE
PIP STUFF.CMD;*/DE
PIP *.NEW;*/DE
FLY /RS=RT: 20,1 RESULT.NEW/DO
TIME
RUN FILSR2
LRC L1/CR:375.:100.:100.:00J
FAP QLIB
QSTUFF
PIP RESULT.LIB=L1.OLB/RF
PIP *.OBJ;*/DE
PIP *.FTN;*/DE
PIP LIB.CMD;*/DE
PIP STUFF.CMD;*/DE
PIP *.NEW;*/DE
FLY /RS=RT: 20,1 RECON.NEW/DO
TIME
RUN FILSR2
LRC L1/CR:30.:50.:50.:00J
FAP QLIB
QSTUFF
PIP RECON.LIB=L1.OLB/RF
PIP *.OBJ;*/DE
PIP *.FTN;*/DE
PIP LIB.CMD;*/DE
PIP STUFF.CMD;*/DE
PIP *.NEW;*/DE
FLY /RS=RT: 20,1 CPTH.NEW/DO
TIME
RUN FILSR2
LRC L1/CR:300.:100.:100.:00J
FAP QLIB
```

PLEASE PACK 12 BEST QUALITY BATTERIES
FROM DOWT MANUFACTURED TO A006

```

3STUFF
PIP CONTY.OLB=LL.OLB/DE
PIP *.OB1;*/DE
PIP *.FTN;*/DE
PIP LIB.CMD;*/DE
PIP STUFF.CMD;*/DE
PIP *.NEW;*/DE
FLX /PS=MT: 20,1 DEFS.NEW/DO
TIME
RUN F11002
LPS LI/CR:98.:50.:00J
FAP GLIB
3STUFF
PIP DEFS.OLB=LL.OLB/DE
PIP *.OB1;*/DE
PIP *.FTN;*/DE
PIP LIB.CMD;*/DE
PIP STUFF.CMD;*/DE
PIP *.NEW;*/DE
FLX /PS=MT: 20,1 LOCAL.NEW/DO
TIME
RUN F11002
LPS LI/CR:98.:50.:00J
FAP GLIB
3STUFF
PIP LOCAL.OLB=LL.OLB/DE
PIP *.OB1;*/DE
PIP *.FTN;*/DE
PIP LIB.CMD;*/DE
PIP STUFF.CMD;*/DE
PIP *.NEW;*/DE
FLX /PS=MT: 20,1 CUPS.NEW/DO
TIME
RUN F11002

```



```

LRS 11/CR:70.:50.:001
E4P QLR
DSTUFF
PIP SUGG.OIB=11.01B/DE
PIP *.FTU:*/*DE
PIP *.OB:*/*DE
PIP 11B.CID:*/*DE
PIP STUFF.CID:*/*DE
PIP *.NEU:*/*DE
FLX /RS=IT: 20,1 TRANS.NEU/DO
TIME
DMM FILE02
LRS 11/CR:75.:40.:001
E4P QLR
DSTUFF
PIP TRANS.OIB=11.01B/DE
PIP *.OB:*/*DE
PIP *.FTU:*/*DE
PIP 11B.CID:*/*DE
PIP STUFF.CID:*/*DE
PIP *.NEU:*/*DE
FLX /RS=IT: 20,1 OPTIM.NEU/DO
TIME
DMM FILE02
LRS 11/CR:45.:40.:001
E4P QLR
DSTUFF
PIP OPTIM.OIB=11.01B/DE
PIP *.FTU:*/*DE
PIP *.OB:*/*DE
PIP 11B.CID:*/*DE
PIP STUFF.CID:*/*DE
PIP *.NEU:*/*DE
FLX /RS=IT: 20,1 SECC.NEU/DO

```


ACK QUES DO YOU WANT TO COLLECT THE LICENSES, YOU
WILL QUES .5000 000
P10 4.0102*/82
.200:

ALL INFORMATION CONTAINED
HEREIN IS UNCLASSIFIED
DATE 01-10-2001 BY 60321

APPENDIX F

LISTING OF GIFTS TAPES (NPS VERSION)

The following are listings of the contents of the tapes needed by BUILDG.CMD to build GIFTS. Though all the files could have fit on one tape, the method of dividing them was used to make the reading process more efficient. In general, the source listings are on REC: (RE:) and the CMD, ODI and existing TSK files are on RE1:.

The files were created under the PLM utility of ASK-111 in DOS format.

LISTING OF MT0:

DIRECTORY
01-SEP-80

MT0:[20,1]

LIBR1.NEW	125.	01-SEP-80
LIBR2.NEW	172.	01-SEP-80
LIBR3.NEW	172.	01-SEP-80
LIBR4.NEW	260.	01-SEP-80
LIBR5.PDP	166.	01-SEP-80
BULKLB.NEW	351.	01-SEP-80
BULKH.NEW	577.	01-SEP-80
EDITM.NEW	449.	01-SEP-80
BULKF.NEW	20.	01-SEP-80
EDITLB.NEW	263.	01-SEP-80
STIFF.NEW	164.	01-SEP-80
DECOM.NEW	23.	01-SEP-80
STRESS.NEW	229.	01-SEP-80
AUTOL.NEW	26.	01-SEP-80
RESULT.NEW	544.	01-SEP-80
TRAN1.NEW	24.	01-SEP-80
TRAN2.NEW	26.	01-SEP-80
REDCS.NEW	104.	01-SEP-80
LOCAL.NEW	120.	01-SEP-80
SAVEK.NEW	8.	01-SEP-80
RESIDU.NEW	20.	01-SEP-80
PRINT.NEW	20.	01-SEP-80
TEST.NEW	2.	01-SEP-80
BULKS.NEW	646.	01-SEP-80
LOADS.NEW	551.	01-SEP-80
OPTIM.NEW	52.	01-SEP-80
DEFL.NEW	115.	01-SEP-80
TRANS.NEW	91.	01-SEP-80
DEFCO.NEW	152.	01-SEP-80
TEST2.NEW	3.	01-SEP-80
TSTPLT.NEW	6.	01-SEP-80
SUBS.NEW	52.	01-SEP-80

TOTAL OF 5533. BLOCKS IN 32. FILES

LISTING OF MT1:

DIRECTORY
01-SEP-80

MT1:C20,17

FILSR2.TSK	57.	01-SEP-80
EST.TSK	56.	01-SEP-80
STUFFE.TSK	41.	01-SEP-80
BUILD.CMD	9.	01-SEP-80
BUILD.T.CMD	10.	01-SEP-80
EST.CMD	1.	01-SEP-80
STIFF.CMD	1.	01-SEP-80
SUBS.CMD	1.	01-SEP-80
TRAN1.CMD	1.	01-SEP-80
TRANS.CMD	1.	01-SEP-80
OPTIM.CMD	1.	01-SEP-80
STRESS.CMD	1.	01-SEP-80
EDITLB.CMD	1.	01-SEP-80
SAVEK.CMD	1.	01-SEP-80
PRINT.CMD	1.	01-SEP-80
RESIDU.CMD	1.	01-SEP-80
TRAN2.CMD	1.	01-SEP-80
REDCS.CMD	1.	01-SEP-80
GIFTSS.CMD	1.	01-SEP-80
BULKM.CMD	1.	01-SEP-80
BULKLB.CMD	1.	01-SEP-80
DEFL.CMD	1.	01-SEP-80
RESULT.CMD	1.	01-SEP-80
BULKF.CMD	1.	01-SEP-80
EDITH.CMD	1.	01-SEP-80
AUTOL.CMD	1.	01-SEP-80
DECOM.CMD	1.	01-SEP-80
DEFC.S.CMD	1.	01-SEP-80
LOCAL.CMD	1.	01-SEP-80
BUILD.D.CMD	10.	01-SEP-80
DECOM.ODL	1.	01-SEP-80
OPTIM.ODL	1.	01-SEP-80
BULKM.ODL	3.	01-SEP-80
BULKLB.ODL	2.	01-SEP-80
DEFL.ODL	2.	01-SEP-80
EDITH.ODL	2.	01-SEP-80
LOCAL.ODL	1.	01-SEP-80
SUBS.ODL	1.	01-SEP-80
DEFC.S.ODL	1.	01-SEP-80
TRANS.ODL	1.	01-SEP-80
STRESS.ODL	1.	01-SEP-80
STIFF.ODL	2.	01-SEP-80
REDCS.ODL	1.	01-SEP-80
RESULT.ODL	3.	01-SEP-80
EDITLB.ODL	1.	01-SEP-80
GIFTSS.INF	197.	01-SEP-80
EST.FTN	2.	01-SEP-80
FILSR.FTN	21.	01-SEP-80
FILSR2.FTN	13.	01-SEP-80
STUFFE.FTN	6.	01-SEP-80
FILSR.TSK	51.	01-SEP-80

TOTAL OF 520. BLOCKS IN 51. FILES

BIBLIOGRAPHY

- Digital Equipment Corporation, FORTAN Four-Plus, User's Guide, 1977.
- Digital Equipment Corporation, PDP-11 FORTRAN, Language Reference Guide, 1977.
- Digital Equipment Corporation, RSX-11M, Beginner's Guide, 1977.
- Digital Equipment Corporation, RSX-11M, Task Builder Reference Manual, 1978.
- McKhouse, R. H. Jr., Morris, D. R., Minicomputer Systems, Organization, Programming and Applications (PDP-11), 2d Ed., Prentice-Hall, 1979.
- Rogers, D. E., Adams, J. A., Mathematical Elements for Computer Graphics, McGraw-Hill, 1976.
- Zienkiewicz, O. C., The Finite Element Method, 3d Ed., McGraw-Hill, 1977.

INITIAL DISTRIBUTION LIST

	No. Copies
1. Defense Technical Information Center Cameron Station Alexandria, Virginia 22314	2
2. Library, Code 0142 Naval Postgraduate School Monterey, California 93940	2
3. Department Chairman, Code 69 Department of Mechanical Engineering Naval Postgraduate School Monterey, California 93940	1
4. Professor Gilles Cantin, Code 69CI Department of Mechanical Engineering Naval Postgraduate School Monterey, California 93940	5
5. Professor Hussein A. Hamel University of Arizona College of Engineering Aerospace and Mechanical Engineering Department Interactive Graphics Engineering Laboratory AME Building, Room 210 Tucson, Arizona 85721	2
6. LCDR John T. Sheldon, USN 218 Camino Entrada Chula Vista, California 92010	1
7. Professor George A. Rahe, Code 52Ra Department of Computer Science Naval Postgraduate School Monterey, California 93940	1

DATE
FILMED
-8